

DECLARATION OF CONFORMITY

We,

Forbo Flooring
 Industrieweg 12
 1566 JP ASSENDELFT
 The Netherlands

Assendelft, 14-02-2005

Declare that the product Corkment is in conformity with the requirements in the following table when tested in accordance with the methods given therein.

Property	Requirements			Test method
	2.0 mm	3.2 mm	6.0 mm	
Nominal Thickness	2.0 mm	3.2 mm	6.0 mm	
Thickness	2.0 ± 0.20 mm	3.2 ± 0.20 mm	6.0 ± 0.20 mm	EN 428
Width	Min. stated value	Min. stated value	Min. stated value	EN 426
Length	Min. stated value	Min. stated value	Min. stated value	EN 426
Weight	1.3 kg/m ² (± 10%)	2.1 kg/m ² (± 10%)	3.9 kg/m ² (± 10%)	EN 430
Residual Indentation	Max. 0.30 mm	Max. 0.40 mm	Max. 0.70 mm	EN 433
Flexibility	Ø 30 mm	Ø 40 mm	Ø 50 mm	EN 435, method A
Thermal resistance	Ca. 0.032 m ² K/W	Ca. 0.045 m ² K/W	Ca. 0.060 m ² K/W	DIN 52612
Fire resistance	Class F _{fl}	Class F _{fl}	Class F _{fl}	EN 13501-1
Density	Max. 750 kg/m ₃	Max. 750 kg/m ₃	Max. 750 kg/m ₃	EN 436

Our certified quality assurance system complying with ISO 9001 ensures the control over all activities affecting the quality of the products, to meet all requirements.

F.W. Seifert
 Manager Quality Assurance