

# nuway<sup>®</sup> tuftiguard HD nuway<sup>®</sup> tuftiguard HD FR

## Technical specifications

Nuway tuftiguard HD – plain, classic, design and FR

Maximum length per module	2500mm	
Maximum width per module	750mm	
Maximum weight per module	23kg/m <sup>2</sup>	
Depth	12mm	17mm
Scraper bar material	Aluminium	Aluminium
Construction	Closed	Closed
Number of wiper strips	2	2
Total weight (kg/m <sup>2</sup> )	17	24
Max static load (kg/cm <sup>2</sup> )	900	900
Dynamic load (kg) 2 wheels 80mm, 20,000 passes	350	350
Fire behaviour EN13501-1	C <sub>fl</sub> -s1 (with FR rubber)	B <sub>fl</sub> -s1 (with FR rubber)
Frames	A selection of recessed matwell frames are available, please see page 55 for details	
Ramp frame model	ARF 50	ARF 70
Manufacturing method	Entrance flooring system with scraper bars and rubber wiper strips	
Wiper designs	Plain, grey fibres, coloured fibres	
Wiper material	Rubber	
Pile material	100% Polyamide BCF	

To find out more about how our Nuway ranges help to create better environments, please visit our web site and download the environmental data sheets [www.forbo-flooring.co.uk/cbedownloads](http://www.forbo-flooring.co.uk/cbedownloads)