

# Technical specifications

Allura Colour meets the requirements of EN-ISO 10581 - Type 1

	Total thickness	EN-ISO 24346	2.0 mm
	Collection size		24
	Commercial use	EN-ISO 10874	34, very heavy
	Industrial use	EN-ISO 10874	43, heavy
	Tile size	EN-ISO 24342	610 x 610 mm
	Total weight	EN-ISO 23997	3.1 kg/m <sup>2</sup>
	Dimensional stability	EN-ISO 23999	0,05 %
	Residual indentation	EN-ISO 24343-1	≤0,04 mm
	Castor chair continuous use	ISO 4918/EN 425	no effect
	Light fastness	EN-ISO 105-B02	≥ 6
	Resistance to chemicals	EN-ISO26987	excellent
	VOC emissions	AgBB / DIBT	suitable for indoor applications
	Slip resistance	DIN 51130	R9

Allura Colour meets the requirements of EN 14041

EN 14041  
  
 0200130\_DOP\_306

	Reaction to fire	EN 13501-1	B <sub>n</sub> -s1
	Slip resistance	EN 13893	DS - μ ≥ 0.50
	Thermal conductivity	EN 12524	0.25 W/(m.K)
	Static electrical propensity	EN 1815	≤ 2 kV

The above information is subject to modifications for the benefit of further improvements

The quality and environmental management system of Forbo Coevorden B.V. (NL) and Forbo Giubiasco S.A. (CH) where Forbo Allura is manufactured are certified in accordance with ISO 9001 and ISO 14001

