

UP 6E GSTR/GL BLACK/TRANSPARENT



Sketch of cross-section (not actual size)

Applications

- Folding machine web-offset newspaper / coldset
- Compensating stacker (coldset)
- Trimmer (Rotative & 3- knife)
- Postpress / Mailroom / Bindery
- Can conveying
- Machine tape

Advantages

- Polyamide coating specifically for the transportation of wetprint products
- Low ink take-up rate
- High wear resistance polyamide surface
- Easy and fast splicing method:
Wedge splice ADV01
Z-Splice ADV09 (no glue)
- Edge stable
- Good tracking characteristics due to transversal strength

Basic technical data

Drive face	Urethane
Top face / operational face	Polyamide
Article no.	822134
d _{min} (mm)	30 (24mm up to 6m/s)
Total thickness (mm)	1.2 +/- 0,1
Shaft load (N/mm width)	5 (1% elongation, 180°)
Weight (kg/m ²)	1.3

Product Quick Info EX-822134-2 · 01/13
FMS · Reproduction of text or parts thereof only
with our approval.
Modifications reserved.

Forbo Siegling GmbH
Lilienthalstraße 6/8, D-30179 Hannover
Telefon +49 511 67 04 0, Fax +49 511 67 04 305
www.forbo-siegling.com, siegling@forbo.com