

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Härter PU-LOT
- **Article number:** 49532
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
FORBO Eurocol Deutschland GmbH
August-Roebling-Str. 2
D-99091 Erfurt
Tel.: +49 (0)361 73041-0
Fax: +49 (0)361 73041-92
Website: <http://www.forbo-bonding.de>
- **Further information obtainable from:**
Laboratory
Ronny Dorna
Ronny.Dorna@forbo.com
- **1.4 Emergency telephone number:** GGIZ +49-361-730730 (for Germany)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Carc. 2 H351 Suspected of causing cancer.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 1)

· Hazard pictograms

GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labelling:**

4,4'-methylenediphenyl diisocyanate
 diphenylmethanediisocyanate, isomeres and homologues
 o-(p-isocyanatobenzyl)phenyl isocyanate
 2,2'-methylenediphenyl diisocyanate

· Hazard statements

H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P405 Store locked up.

· Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.
 EUH210 Safety data sheet available on request.
 Restricted to professional users.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 2)

CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-<50%
CAS: 9016-87-9 EINECS: 202-966-0 Index number: 615-005-00-9	diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30-<40%
CAS: 5873-54-1 EINECS: 227-534-9 Index number: 615-005-00-9	o-(p-isocyanatobenzyl)phenyl isocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-<30%
CAS: 2536-05-2 EINECS: 219-799-4 Index number: 615-005-00-9	2,2'-methylenediphenyl diisocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	1-3%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 3)

*In case of fire, the following can be released:**Carbon monoxide and carbon dioxide**Nitrogen oxides (NO_x)***· 5.3 Advice for firefighters****· Protective equipment:** *Wear self-contained respiratory protective device.***SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.**Ensure adequate ventilation**Product forms slippery surface when combined with water.***· 6.2 Environmental precautions:** *Do not allow to enter drains/ surface or ground water.***· 6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to item 13.***· 6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****· 7.1 Precautions for safe handling***Keep receptacles tightly sealed.**Ensure good ventilation/exhaustion at the workplace.**Prevent formation of aerosols.**Do not breathe vapour/aerosol.***· Information about fire - and explosion protection:** *No special measures required.***· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:** *No special requirements.***· Information about storage in one common storage facility:** *Not required.***· Further information about storage conditions:***Protect from frost.**Keep container tightly sealed.**Store in cool, dry conditions in well sealed receptacles.**Protect from humidity and water.**Store under lock and key and with access restricted to technical experts or their assistants only.***· Recommended storage temperature:** *+10 °C - +25 °C***· Storage class:** *10***· 7.3 Specific end use(s)** *No further relevant information available.***SECTION 8: Exposure controls/personal protection****· Additional information about design of technical facilities:** *No further data; see item 7.*

(Contd. on page 5)

*

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 4)

· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****101-68-8 4,4'-methylenediphenyl diisocyanate**

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

2536-05-2 2,2'-methylenediphenyl diisocyanate

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

· **Additional Occupational Exposure Limit Values for possible hazards during processing:****101-68-8 4,4'-methylenediphenyl diisocyanate**

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Chloroprene rubber, CR

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 5)

*Recommended thickness of the material: ≥ 5 mm**The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.***· Penetration time of glove material***For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).**The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.***· Eye protection:***Tightly sealed goggles***· Body protection: Protective work clothing****SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

Form:	Fluid
Colour:	Dark brown
· Odour:	Weak, characteristic

· pH-value: Not applicable.**· Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

· Flash point: > 200 °C**· Flammability (solid, gas):** Not applicable.**· Ignition temperature:** 400 °C**· Decomposition temperature:** Undetermined.**· Auto-ignition temperature:** Product is not selfigniting.**· Explosive properties:** Product does not present an explosion hazard.**· Explosion limits:****Lower:** 0.4 Vol %**· Vapour pressure:** Not determined.**· Density at 20 °C:** 1.225 g/cm³**· Evaporation rate** Not determined.**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Undetermined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 6)

- | | |
|---|--|
| · Viscosity:
Dynamic at 20 °C: | 73 mPas |
| · Solvent content:
Organic solvents: | 0.0 % |
| VOC (CE) | 0.00 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.

· **LD/LC50 values relevant for classification:****101-68-8 4,4'-methylenediphenyl diisocyanate**

Oral	LD50	>2000 mg/kg (rat) (84/449/EWG)
Dermal	LD50	>9400 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	0.368 mg/l (rat) (OECD 403)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Oral	LD50	>10000 mg/kg (rat) (OECD 401)
Dermal	LD50	>9400 mg/kg (rabbit) (OECD 402)

· **ATE (Acute toxicity estimates) - REGULATION (EC) No 1272/2008****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Inhalative	ATE (inhalativ 4h)	1.5 mg/l (rat)
------------	--------------------	----------------

· **Primary irritant effect:**· **Skin corrosion/irritation****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Irritation of skin	Dermal Irritation	irritating (rabbit) (OECD 404)
--------------------	-------------------	--------------------------------

Causes skin irritation.

· **Serious eye damage/irritation****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Irritation of eyes	Eye Irritation	irritating (rabbit) (OECD 405)
--------------------	----------------	--------------------------------

Causes serious eye irritation.

· **Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 7)

- May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity**
Suspected of causing cancer.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
 - **STOT-single exposure**
May cause respiratory irritation.
 - **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
 - **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

101-68-8 4,4'-methylenediphenyl diisocyanate

EC50/48h	>1000 mg/l (Daphnia magna) (OECD 202)
EC50/72h	>1640 mg/l (Scenedesmus suspicatus) (OECD 201)
LC50/96h	>1000 mg/l (zebrafish (Brachydanio rerio)) (OECD 203)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

EC50/24h	>1000 mg/l (Daphnia magna) (OECD 202)
LC50/96h	>1000 mg/l (zebrafish (Brachydanio rerio)) (OECD 203)

· 12.2 Persistence and degradability No further relevant information available.

· Degree of elimination:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Modified MITI Test	0 % / 28d (OECD 302C)
--------------------	-----------------------

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxicological effects:

· Behaviour in sewage processing plants:

Type of test	Effective concentration	Method	Assessment
101-68-8 4,4'-methylenediphenyl diisocyanate			
EC50/3h	>100 mg/l	(activated sludge)	(OECD 209)
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues			
EC50/3h	>100 mg/l	(activated sludge)	(OECD 209)

· Additional ecological information:

· General notes:

- Do not allow product to reach ground water, water course or sewage system.
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 8)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|--|--|
| · 14.1 UN-Number | none |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | Not dangerous according to the above specifications. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 56a, 56b, 56c
- **National regulations:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Water hazard class 3 (Self-assessment): extremely hazardous for water.
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed. (94/33/EC)
Employment restrictions concerning pregnant and lactating women must be observed. (92/85/EC)

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.01.2017

Version number 2

Revision: 09.01.2017

Trade name: Härter PU-LOT

(Contd. of page 9)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

Irritating to skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Laboratory

· **Contact:**

Dr. Amina Chnirheb

Amina.Chnirheb@forbo.com

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**